

Half Cut

BIFACIAL PERC MONOCRYSTALLINE • 120TNB12



High Conversion Efficiency

High panel efficiency to guarantee high power output



Self-Cleaning And Anti-Reflection Glass

Coating glass for self-cleaning reduces surface dust



Outstanding Low Irradiation Glass

Outstanding panel performance even in weak light conditions



Excellent Durability

Wind load up to 2400 Pa, Snow load up to 5400 Pa



0~+5W Positive Power Tolerance




Easy Installation



BIFACIAL

18BB
n-Type



CWT645-120TNB12 645 Wp
CWT640-120TNB12 640 Wp
CWT635-120TNB12 635 Wp
CWT630-120TNB12 630 Wp
CWT625-120TNB12 625 Wp
CWT620-120TNB12 620 Wp
CWT615-120TNB12 615 Wp



30 Years Performance Warranty



12 Years Product Warranty



IEC 61215, IEC 61730-1, IEC 61730-2
ISO 9001:2015, ISO 14001:2015, ISO 45001:2018


ELECTRICAL CHARACTERISTICS

Model Type	CWT615 120TNB12	CWT620 120TNB12	CWT625 120TNB12	CWT630 120TNB12	CWT635 120TNB12	CWT640 120TNB12	CWT645 120TNB12
Peak Power (P _{max})	615 Wp	620 Wp	625 Wp	630 Wp	635 Wp	640 Wp	645 Wp
Module Efficiency (%)	21.73	21.95	22.08	22.26	22.44	22.65	22.79
Maximum Power Voltage (V _{mp})	35.56	35.76	35.96	36.16	36.36	36.56	36.76
Maximum Power Current (I _{mp})	17.30	17.34	17.39	17.43	17.45	17.51	17.55
Open Circuit Voltage (V _{oc})	42.78	42.98	43.18	43.38	43.58	43.78	43.98
Short Circuit Current (I _{sc})	18.24	18.30	18.35	18.40	18.46	18.52	18.57
Power Tolerance	0~+5W						
Maximum System Voltage	1500V DC						
Operating Temperature	-40 ~ +85°C						
Protection Class	Class II						
Maximum Series Fuse Rating	25A						

MECHANICAL SPECIFICATIONS

Cell Dimensions(mm/inch)	210x105 / 8.27x4.14
Cells per Module(pcs)	120 (6x20)
Weight(kg/lbs)	31.0 / 68.35
Panel Dimensions(mm/inch)	2172x1303x35 / 85.51x51.30x1.37
Max. Wind/Snow Load(Pa)/(lb/ft ²)	(2400 / 5400) / (50 / 212)
Junction Box	IP68
Junction Box Cable Length(mm/inch)	350-1600 / 13.78-63.00
Frame Color	Silver / Black
Rear Side Material	Transparent Backsheet

PHYSICAL CHARACTERISTICS



* The specifications are obtained under the standard test conditions: 1000W/m² solar irradiance, 1.5 Air Mass and cell temperature of 25°C. Measurement uncertainty for all panels is 3%. The actual transactions will be subject to the contracts. These parameters are for reference only and it is not a part of the contracts. The technical specifications in this document may vary. For more information, refer to the "Installation Manual".

* For roof, facades and installations on similar surfaces, solar panels should be mounted over a fire-resistant covering suitable for this application, with adequate ventilation between the back of the solar panels and the mounting surface. Improper installations are hazardous and may spark a fire. Solar panels must not be mounted on structures and roofs which are made of not fire-resistant materials such as plastic layer, transparent plastic, PVC or similar materials without any fire-protection layer. Usage and installation not in accordance with the guidelines as outlined in the installation manual will terminate the warranty. Please refer to the installation manual and the warranty documents for further details.

* CW Enerji reserves the right to change the specification of products without prior notice.

REAR SIDE POWER GAIN

(645W Front Power Referenced)

Rear Side Power Gain	5%	10%	15%	20%	25%
Peak Power (P _{max})	677.25	709.50	741.75	774.00	806.25
Short Circuit Current (I _{sc})	19.48	20.38	21.28	22.19	23.10
Open Circuit Voltage (V _{oc})	44.05	44.12	44.19	44.26	44.33
Maximum Power Current (I _{mp})	18.42	19.28	20.14	21.02	21.88
Maximum Power Voltage (V _{mp})	36.77	36.80	36.83	36.85	36.87

TEMPERATURE CHARACTERISTICS

Temp. Coeff. of (I _{sc})	0.040%/°C
Temp. Coeff. of (V _{oc})	-0.260%/°C
Temp. Coeff. of (P _{max})	-0.320%/°C

PACKING CONFIGURATION

Container	40' HQ
Pieces per Pallet	31
Pieces Per Container	527
Pallet Per Container	17

ELECTRICAL CHARACTERISTICS

